



MAUVILAC ANTI-FUNGUS

PRODUCT DATA SHEET

A high quality acrylic co-polymer emulsion paint formulated with a high dosage blend of fungicides and bactericides for maximum resistance.

MAUVILAC ANTI-FUNGUS is highly effective in humid areas.

USAGE

- On cement substrates such as plaster, concrete and building blocks.
- On panel wood and ceiling boards.
- On absorbent wall coverings (wall paper, etc.)
- On foamed polystyrene and on flexible synthetic foam.
- On suitably primed interior wood structures.
- Recommended for interior and exterior application.

PHYSICAL DATA

- **Finish :** Matt
- **Colour :** See Mauvilac Colour Card. (White & Pastel colours only)
- **Consistency :** Viscous Liquid
- **Specific Gravity :** 1.50 – 1.52
- **Volume Solids :** 46% (approx.)
- **Flash Point :** Not Applicable
- **Shelf Life :** 12 months
- **Packing :** 20 L, 5 L

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information

APPLICATION

- **Surface preparation** : See method SP 001
- **Application method** : Apply three coats by roller or brush onto clean, dry and sealed surface. **MAUVILAC ANTI-FUNGUS** can be applied in a single coat by airless or low pressure spray equipment.
- **Dilution** : Thin down with water as required; for best results do not exceed the dilution volume ratio of 1 part water to 5 parts paint.
- **Spreading rate / Film thickness** : One litre of **MAUVILAC ANTI-FUNGUS** will cover between 8 and 10 m² of surface in one coat ; at this spreading rate the dry film thickness will vary between 40 and 50 microns on a completely smooth, non absorbent surface.
- **Drying time** : Approximately 30 minutes to touch dry, **MAUVILAC ANTI-FUNGUS** can be over-coated after approximately 3 hours.
- **Cleaning solvent** : Use water; if necessary add some liquid detergent to warm water.
- **Preceding coat** : Use **MAUVILITH SEALER** or **MAUVIFLEX SEALER** or **CLEAR EMULSION BINDER** as a sealer on new cement substrates and on powdery or absorbent surfaces.
- **Subsequent coat** : Not recommended.

SAFETY

- **MAUVILAC ANTI-FUNGUS** can be safely used in rooms that will be occupied the following day.
- Do not use on baby cribs or children's' toys.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Manufactured and Distributed by:
Mauvilac Industries Ltd
 Pailles Road, Pailles, Republic of Mauritius
 Tel: (230) 206 4700
 Fax: (230) 286 5315

JULY 2004