



## MAUVILAC SOLVENTS/THINNERS

### PRODUCT DATA SHEETS

PRODUCT NAME / CODE	DESCRIPTION AND USE	SPECIFIC GRAVITY	FLASH POINT
<b>AROMATIC SOLVENT</b>	Aromatic hydrocarbon solvent for use as a diluent or cleaning solvent for <b>ROAD MARKING</b> and <b>CHLORINATED RUBBER PAINTS</b>	0.89 - 0.91	25°C Closed Cup
<b>DD LACK THINNER</b>	A blend of organic solvents for use as a diluent or cleaning solvent for <b>DD LACK</b> product range.	0.97 - 0.99	<23°C Closed Cup
<b>EPOXY THINNER</b>	A blend of organic solvents for use as a diluent or cleaning solvent for <b>EPOXY</b> product range and for <b>HIGH TECH 332 PRIMERS</b> .	0.79 - 0.81	<23°C Closed Cup
<b>ETCH THINNER</b>	A blend of organic solvents for use as a diluent or cleaning solvent for <b>TWO PACK ETCH PRIMER</b> and <b>MA 10 PRIMER</b>	0.79 - 0.81	<23°C Closed Cup
<b>TEST BENZIN</b>	Aliphatic hydrocarbon solvent for use as a diluent or cleaning solvent for the following product range:- <b>ALKYD, MAUVILITH, MAUVI N' ONE, BITUMEN AND TAR</b> (Not to be used with <b>ROAD MARKING PAINT</b> )	0.75 - 0.80	38° C Closed Cup
<b>ACID CATALYSED THINNER</b>	A blend of organic solvents for use as a diluent or cleaning solvent for <b>ACID CATALYSED PRODUCTS</b>	0.73 - 0.77	<23°C Closed Cup
<b>COACH ENAMEL THINNER</b>	Fast evaporating aromatic solvent for use as a diluent and cleaning solvent for <b>COACH ENAMEL PRIMER</b> and <b>COACH ENAMEL</b> .	0.86 – 0.87	<23°C Closed Cup
<b>HAMMER THINNER</b>	A blend of organic solvents for use as a diluent and cleaning solvent for <b>HAMMER FINISH</b> .	0.87 – 0.89	<23°C Closed Cup
<b>KARNAMEL THINNER</b>	A blend of organic solvents for use as a diluent or cleaning solvent for <b>KARNAMEL</b> primers and topcoats. It can be used as a cleaning solvent for other specified solvent.	0.90 – 0.94	<23°C Closed Cup

PRODUCT NAME / CODE	DESCRIPTION AND USE	SPECIFIC GRAVITY	FLASH POINT
<b>KARNAMEL RETARDER</b> Product code : 9500	Slow evaporating solvent that can be added to <b>KARNAMEL THINNER</b> to prevent film defects such as blushing under adverse ambient conditions. Can also be used solely.	0.93 – 0.99	<23°C Closed Cup
<b>ACRYLINE THINNER SLOW (ATH 310) FAST (ATH 302)</b>	Blend of organic solvents for use as diluents for ACRYLINE PRODUCTS. A fast and slow evaporating thinner is available to obtain optimum results depending on ambient conditions at time of application.	0.89 - 0.91	25°C Closed Cup
<b>NITRO THINNER</b>	A blend of organic solvents for use as a diluent or cleaning solvent for <b>NITRO SANDING SEALER, NITRO WOOD SEALER.</b>	0.86 - 0.88	< 23°C Closed Cup
<b>INACEL THINNER</b>	A blend of organic solvents for use as a diluent for <b>INACEL VARNISHES</b> to obtain optimum results. Can be used also as cleaning solvent.	0.86 - 0.88	<23°C Closed Cup
<b>FLOWLINE THINNER</b>	A blend of organic solvents for use as a diluent or cleaning solvent for <b>FLOWLINE</b> primers and topcoats.	0.89 – 0.91	<23°C Closed Cup

- **THINNERS** are flammable, keep away from ignition source, do not smoke whilst using.
- Wear adequate protective equipment, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical attention if necessary.
- Keep containers tightly closed and away from children.
- Thinners are highly flammable and should be used with caution.

Contact your supplier for further information.

These recommendations are means as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

This data sheet supersedes those previously issued and may be changed without prior notice

Manufactured and distributed by  
Mauvilac Industries Ltd  
Motorway M2, Pailles  
Republic of Mauritius  
Tel: (230) 206 4700  
Fax: (230) 286 5315