



EMULSION CASHMERE

PRODUCT DATA SHEET

EMULSION CASHMERE is an acrylic copolymer emulsion paint with an attractive smooth slight silk finish. It is a decorative and protective coating primarily selected for its exceptional performance, long life and long term economical advantage. It is recommended for the interior and exterior of homes, offices, factories, shops, hotels and other related structures. The outstanding washability and scrubability property of **EMULSION CASHMERE** makes it ideal as an interior coating. It is effective in its resistance against fungus in humid areas.

EMULSION CASHMERE is available on **MAUVIMATCH** tinting system.

USAGE

- On cement substrates such as plaster, concrete and building blocks.
- On panel wood and ceiling boards.
- On absorbent wall coverings (wall paper, etc.)
- On foamed polystyrene and on flexible synthetic foam.
- On suitably primed interior wood structures.
- Recommended for interior and exterior applications.

PHYSICAL DATA

- **Finish :** Low gloss-satin
- **Colour :** In excess of 1000 MAUVIMATCH colours.
Consult colour card
- **Consistency :** Medium viscosity liquid
- **Specific gravity :** 1.20 – 1.35
- **Volume Solids :** 30 % - 35%
- **Flash Point :** Not Applicable
- **Packing :** 1, 5, 20 L

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information.

APPLICATION

- **Surface preparation:** See method SP 001
- **Application method:** Apply two to three coats by roller or brush onto clean, dry, sound and sealed surface. **EMULSION CASHMERE** can be applied using airless or low-pressure spray equipment.
- **Dilution:** Thin down with water as required; for best results do not exceed the dilution volume ratio of 1 part water to 10 parts paint.
- **Spreading rate / Film thickness:** One litre of **EMULSION CASHMERE** will cover between 6 and 8 m² of surface in one coat ; at this spreading rate the dry film thickness will vary between 55 and 40 microns on a completely smooth, non absorbent surface.
- **Drying time:** Approximately 30 minutes to touch dry, **EMULSION CASHMERE** can be over-coated after approximately 4 to 5 hours.
- **Cleaning solvent:** Use water; if necessary add some liquid detergent to warm water.
- **Preceding coat:** Apply one coat of **MAUVILITH SEALER** or **MAUVIFLEX SEALER** or **CLEAR EMULSION BINDER** on powdery or absorbent surfaces for good adhesion.
- **Subsequent coat:** Not required.

SAFETY

- **EMULSION CASHMERE** can be safely used in rooms that will be occupied the following day or where foodstuff is stored or processed.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Manufactured and Distributed by:
Mauvilac Industries Ltd
Pailles Road, Pailles, Republic of Mauritius
Tel: (230) 206 4700
Fax: (230) 286 5315

June 2002