



CLEAR EMULSION BINDER

PRODUCT DATA SHEET

An acrylic based, alkali resistant emulsion sealer for application directly onto the substrate. **CLEAR EMULSION BINDER** will penetrate the substrate to provide a basis for good adhesion of subsequent coatings.

USAGE

- On cement substrates such as plaster, concrete and building blocks.
- On ceiling boards and interior panel wood.
- On absorbent wall coverings (wall paper, etc.)
- On an old coatings which may have chalked; apply **CLEAR EMULSION BINDER** after thorough washing, rinsing and drying.
- On previously lime washed surfaces after thorough washing, rinsing and drying.
- On bituminous and tar surfaces.
- Recommended for interior and exterior use.

PHYSICAL DATA

- **Product Code:** 0008
- **Finish :** Transparent
- **Colour :** Clear , colourless
- **Consistency :** Low viscosity liquid
- **Specific Gravity :** 1.01 (approx.)
- **Volume Solids :** 20% (approx.)
- **Flash Point :** Not Applicable
- **Shelf Life :** 12 months
- **Packing :** 20 L, 5 L, 2 L, 1 L

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information.

APPLICATION

- **Surface preparation** : See method SP 001
- **Application method** : Apply one coat by brush , roller or spray onto a clean, dry surface.
- **Dilution** : **CLEAR EMULSION BINDER** can be applied without dilution. Should dilution be necessary, do not exceed the volume ratio of 1 part of water to 10 parts of the product.
- **Spreading rate / Film thickness** : One litre of **CLEAR EMULSION BINDER** will cover between 5 and 7 m² of surface in one coat ; at this spreading rate the dry film thickness will vary between 30 and 40 microns on a completely smooth, non absorbent surface.
- **Drying time** : Approximately 30 minutes to touch dry, **CLEAR EMULSION BINDER** can be over-coated after approximately 3 hours.
- **Cleaning solvent** : Use water; if necessary add some liquid detergent to warm water.
- **Preceding coat** : Not required.
- **Subsequent coat** : Emulsion paints

SAFETY

- **CLEAR EMULSION BINDER** can be safely used in rooms that will be occupied the following day or where food stuff are stored or processed.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Manufactured and Distributed by:
Mauvilac Industries Ltd
 Pailles Road, Pailles, Republic of Mauritius
 Tel: (230) 206 4700
 Fax: (230) 286 5315

JULY 2002