

ECOWHITE

PRODUCT DATA SHEET

A low cost general purpose acrylic copolymer emulsion paint. **ECOWHITE** is easy to apply and dries quickly to a matt finish.

ECOWHITE can be used where an economical coating is required, it is recommended as a cost effective coating for ceilings and surfaces which are normally subjected to low wear and tear levels.

USAGE

- On properly sealed cement substrates such as plaster, concrete and building blocks.

PHYSICAL DATA

- | | |
|-----------------------------|----------------|
| • Finish : | Matt |
| • Colour : | White |
| • Consistency : | Viscous Liquid |
| • Specific Gravity : | 1.40 (approx.) |
| • Volume Solids : | 28% (approx.) |
| • Flash Point : | Not Applicable |
| • Shelf Life : | 12 months |
| • Packing : | 20 L, 5 L |

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information.

APPLICATION

- **Surface preparation** : Remove dust, chalk, loosely adhering old paint, fungus, mould, oil, grease and any contaminant by scraping, washing, etc. Rinse and allow to dry. On surfaces which have chalked, apply one dilute coat of **CLEAR EMULSION BINDER** before painting.
- **Application method** : Apply two to three coats by roller, brush or spray onto clean, dry and sealed surface.
- **Dilution** : For ease of application, use water for dilution.
- **Spreading rate / Film thickness** : 7 – 9 m² per litre on a completely smooth, non absorbent surface.
- **Drying time** : Approximately 30 minutes to touch dry, **ECOWHITE** can be over-coated after approximately 3 hours.
- **Cleaning solvent** : Use water; if necessary add some liquid detergent to warm water.

SAFETY

- **ECOWHITE** can be safely used in rooms that will be occupied the following day or where food stuff are stored or processed.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.
- Do not use the empty container to store food or drinks.
- Do not dispose paint in drains, rivers, dams or sea.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Manufactured and Distributed by:
Mauvilac Industries Ltd
 Pailles Road, Pailles, Republic of Mauritius
 Tel: (230) 206 4700
 Fax: (230) 286 5315

October 2006