



MAUVILAC SOLVENTS/THINNERS

PRODUCT DATA SHEETS

PRODUCT NAME / CODE	DESCRIPTION AND USE	SPECIFIC GRAVITY	FLASH POINT
AROMATIC SOLVENT	Aromatic hydrocarbon solvent for use as a diluent or cleaning solvent for ROAD MARKING and CHLORINATED RUBBER PAINTS	0.89 - 0.91	25°C Closed Cup
DD LACK THINNER	A blend of organic solvents for use as a diluent or cleaning solvent for DD LACK product range.	0.97 - 0.99	<23°C Closed Cup
EPOXY THINNER	A blend of organic solvents for use as a diluent or cleaning solvent for EPOXY product range and for HIGH TECH 332 PRIMERS .	0.79 - 0.81	<23°C Closed Cup
ETCH THINNER	A blend of organic solvents for use as a diluent or cleaning solvent for TWO PACK ETCH PRIMER and MA 10 PRIMER	0.79 - 0.81	<23°C Closed Cup
TEST BENZIN	Aliphatic hydrocarbon solvent for use as a diluent or cleaning solvent for the following product range:- ALKYD, MAUVILITH, MAUVI N' ONE, BITUMEN AND TAR (Not to be used with ROAD MARKING PAINT)	0.75 - 0.80	38° C Closed Cup
ACID CATALYSED THINNER	A blend of organic solvents for use as a diluent or cleaning solvent for ACID CATALYSED PRODUCTS	0.73 - 0.77	<23°C Closed Cup
COACH ENAMEL THINNER	Fast evaporating aromatic solvent for use as a diluent and cleaning solvent for COACH ENAMEL PRIMER and COACH ENAMEL .	0.86 – 0.87	<23°C Closed Cup
HAMMER THINNER	A blend of organic solvents for use as a diluent and cleaning solvent for HAMMER FINISH .	0.87 – 0.89	<23°C Closed Cup
KARNAMEL THINNER	A blend of organic solvents for use as a diluent or cleaning solvent for KARNAMEL primers and topcoats. It can be used as a cleaning solvent for other specified solvent.	0.90 – 0.94	<23°C Closed Cup

PRODUCT NAME / CODE	DESCRIPTION AND USE	SPECIFIC GRAVITY	FLASH POINT
KARNAMEL RETARDER Product code : 9500	Slow evaporating solvent that can be added to KARNAMEL THINNER to prevent film defects such as blushing under adverse ambient conditions. Can also be used solely.	0.93 – 0.99	<23°C Closed Cup
ACRYLINE THINNER SLOW (ATH 310) FAST (ATH 302)	Blend of organic solvents for use as diluents for ACRYLINE PRODUCTS. A fast and slow evaporating thinner is available to obtain optimum results depending on ambient conditions at time of application.	0.89 - 0.91	25°C Closed Cup
NITRO THINNER	A blend of organic solvents for use as a diluent or cleaning solvent for NITRO SANDING SEALER, NITRO WOOD SEALER.	0.86 - 0.88	< 23°C Closed Cup
INACEL THINNER	A blend of organic solvents for use as a diluent for INACEL VARNISHES to obtain optimum results. Can be used also as cleaning solvent.	0.86 - 0.88	<23°C Closed Cup
FLOWLINE THINNER	A blend of organic solvents for use as a diluent or cleaning solvent for FLOWLINE primers and topcoats.	0.89 – 0.91	<23°C Closed Cup

- **THINNERS** are flammable, keep away from ignition source, do not smoke whilst using.
- Wear adequate protective equipment, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical attention if necessary.
- Keep containers tightly closed and away from children.
- Thinners are highly flammable and should be used with caution.

Contact your supplier for further information.

These recommendations are means as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

This data sheet supersedes those previously issued and may be changed without prior notice

Manufactured and distributed by
Mauvilac Industries Ltd
Motorway M2, Pailles
Republic of Mauritius
Tel: (230) 206 4700
Fax: (230) 286 5315