



INATEINTE

PRODUCT DATA SHEET

INATEINTE is a range of solvent soluble wood stains and tints used for enhancing the appearance of wood.

- Available as a range of 7 base tints - Red, Orange, Yellow, Green, Blue, Brown, Black.
- Available as 6 standard wood tints Teak - Mahogany, Sapele, Prune, Acajou, Walnut, Dark Oak.

USAGE

- For tinting bare wood in the decorative and handicraft sector.
- For enhancing and improving the appearance of timber used in the furniture industry.
- As wood stains miscible with solvent based wood sealers.
- For interior use.

Note : **INATEINTE** dyes should not be used on timber which are exposed to direct sunlight. They will tend to fade out.

Some tints may discolour in the short or medium term when **INATEINTE** is mixed with acidic products such as those from the ACID CATALYSED range. It is advisable to check for discoloration before proceeding.

PHYSICAL DATA

- **Product Codes :** 9900
- **Finish :** Not applicable
- **Colour :** 7 base tints which can be mixed to produce custom colours. 6 Standard wood tints .
- **Consistency :** Liquid
- **Specific Gravity :** 0.8 Approx.
- **Volume Solids :** Not applicable
- **Flash Point :** < 23 °C, closed cup
- **Shelf Life :** 12 months
- **Packing :** 20 L, 5 L, 2 L, 1 L, 500 ml, 250 ml

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information

APPLICATION

- **Surface preparation** : See method SP 002 for wood.
- **Application method** : Apply **INATEINTE** uniformly by brush, cloth pad or conventional spray onto base wood. After checking compatibility, **INATEINTE** can also be mixed to solvent based wood sealers to obtain wood stains for application by brush or conventional spray.
- **Dilution** : Not recommended. Dilute with **D/D LACK THINNER** to lower the tinting strength if necessary.
- **Spreading rate / Film thickness** : Not applicable.
- **Drying time** : Approximately 5 - 10 minutes
- **Cleaning solvent** : **D/D LACK THINNER**
- **Preceding coat** : None.
- **Subsequent coat** : Any clear wood sealer or topcoat.

SAFETY

- **INATEINTE** is flammable, keep away from ignition source. Do not smoke whilst using.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.
- A complete Material Safety Data Sheet is available on request.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

December 1997