



MAUVILITH

PRODUCT DATA SHEET

A high quality solvent soluble ACRYLIC paint for cement based, concrete and plaster surfaces.

- **MAUVILITH** is available in 62 standard colours.

MAUVILITH is an alkali resistant, decorative and protective coating primarily selected for its exceptional performance, long life and long term economical advantage. It is recommended for homes, offices, factories, shops, hotels and other related structures. Over many years of practical experience in Mauritius, **MAUVILITH** has proved to be highly effective in its resistance against fungus growth in humid areas and against Ultra Violet rays in hot/dry regions.

MAUVILITH is easy to apply and dries rapidly to a hard, tough, washable and resistant matt finish. It is self-cleaning due to its typical tendency to chalk when exposed to sunlight, through this process **MAUVILITH** does not retain dirt, dust and organic particles which normally promote fungus growth.

USAGE

- On cement substrates such as plaster, concrete and building blocks.
- In humid regions to discourage fungus and algae growth.
- In dry regions for a permanently clean surface.
- For interior use.
- Highly popular and effective on exterior surfaces.

PHYSICAL DATA

- **Product Code :** 3300
- **Finish :** Matt
- **Colour :** 62 standard colours including black and white.
- **Consistency :** Semi Viscous Liquid
- **Specific Gravity :** 1.29 (approx.)
- **Volume Solids :** 33% (approx.)
- **Flash Point :** 38 ° C (closed cup)
- **Shelf Life :** 12 months
- **Packing :** 20 L, 5 L, 2 L, 1 L.

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information

APPLICATION

- **Surface preparation** : See method SP 001
- **Application method** : Apply two to three coats by roller or brush onto clean, and dry surfaces. Low pressure or airless spray equipment can also be used.
- **Dilution** : Thin down with **TEST BENZIN** as required. For best results do not exceed the dilution volume ratio of 1 part of **TEST BENZIN** to 8 parts of paint.
- **Spreading rate / Film thickness** : One litre of **MAUVILITH** will cover between 6 and 8 m² of surface in one coat ; at this spreading rate the dry film thickness will vary between 55 and 41 microns on a completely smooth, non absorbent surface.
- **Drying time** : Approximately 30 minutes to touch dry, **MAUVILITH** can be over-coated after approximately 6 hours.
- **Cleaning solvent** : **TEST BENZIN**
- **Preceding coat** : Apply one coat of **MAUVILITH SEALER** diluted with **TEST BENZIN** at the rate of 4 : 1 by volume.
- **Subsequent coat** : Not required.

SAFETY

- **MAUVILITH** is flammable, keep away from ignition source. Do not smoke whilst using.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.
- A complete Material Safety Data Sheet is available on request.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Manufactured and Distributed by:
Mauvilac Industries Ltd
 Pailles Road, Pailles, Republic of Mauritius
 Tel: (230) 206 4700
 Fax: (230) 212 4308

June 2007