



# MAUVILITH SEALER

## PRODUCT DATA SHEET

A high quality solvent soluble ACRYLIC sealer for cement based, concrete and plaster surfaces.

**MAUVILITH SEALER** is an alkali resistant penetrating sealer for use as an adhesion promoter on new or aged masonry surfaces. It will also bind and strengthen weak and powdery surfaces as well as coatings which have chalked. **MAUVILITH SEALER** provides a good foundation for the adhesion of subsequent coats of paints.

### USAGE

- On cement substrates such as plaster, concrete and building blocks.
- On aged substrates which may have become weak and powdery.
- On previous painted surfaces which may have chalked.
- On lime-wash which has been thoroughly washed and scrubbed.
- For interior and exterior use.
- Highly popular and effective on exterior surfaces.

### PHYSICAL DATA

- **Product Code :** 3000
- **Finish :** Matt
- **Colour :** White, translucent
- **Consistency :** Semi Viscous Liquid
- **Specific Gravity :** 0.96 (approx.)
- **Volume Solids :** 27% (approx.)
- **Flash Point :** 38 ° C (closed cup)
- **Shelf Life :** 12 months
- **Packing :** 20 L, 5 L, 2 L, 1 L.

Paints should be stirred before use and occasionally whilst in use.  
Contact your supplier for further information

### APPLICATION

- **Surface preparation** : See method SP 001
- **Application method** : Apply one coat by roller or brush onto clean, and dry surfaces. Low pressure or airless spray equipment can also be used.
- **Dilution** : Thin down with **TEST BENZIN** as required. For best results dilute by volume with one part **TEST BENZIN** to four parts of **MAUVILITH SEALER**.
- **Spreading rate / Film thickness** : One litre of **MAUVILITH SEALER** will cover between 9 and 11 m<sup>2</sup> of surface in one coat ; at this spreading rate the dry film thickness will vary between 30 and 25 microns on a completely smooth, non absorbent surface.
- **Drying time** : Approximately 30 minutes to touch dry, **MAUVILITH SEALER** can be over-coated after approximately 6 hours.
- **Cleaning solvent** : **TEST BENZIN**
- **Preceding coat** : Not required.
- **Subsequent coat** : **MAUVILITH** or **MAUVITOP** or any other emulsion based paints.

#### **SAFETY**

- **MAUVILITH SEALER** is flammable, keep away from ignition source. Do not smoke whilst using.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.
- A complete Material Safety Data Sheet is available on request.

#### **MAINTENANCE**

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Manufactured and Distributed by:  
**Mauvilac Industries Ltd**  
 Pailles Road, Pailles, Republic of Mauritius  
 Tel: (230) 206 4700  
 Fax: (230) 212 4308

June 2007