



MAUVINYL

PRODUCT DATA SHEET

A low cost vinyl copolymer emulsion (PVA) paint with good hiding power. It is easy to apply and dries quickly to a matt finish.

- **MAUVINYL** is available in white, black and a range of some 30 Standard Pastel Colours.

MAUVINYL is a decorative paint used as an economical coating for homes, offices, shops and other related structures. It is recommended as a cost effective coating for ceilings and other interior surfaces which are normally subjected to low wear and tear levels.

USAGE

- On sealed cement substrates such as plaster, concrete and building blocks.
- On sealed panel wood and ceiling boards.
- On sealed absorbent wall coverings (wall paper, etc.)
- On foamed polystyrene.
- Recommended for interior use.

PHYSICAL DATA

- **Product Code :** 0300
- **Finish :** Matt
- **Colour :** Approximately 30 standard pastel colours, black and white.
- **Consistency :** Viscous Liquid
- **Specific Gravity :** 1.50 (approx.)
- **Volume Solids :** 33% (approx.)
- **Flash Point :** Not Applicable
- **Shelf Life :** 12 months
- **Packing :** 20 L, 5 L, 2 L, 1 L

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information.

APPLICATION

- **Surface preparation** : See method SP 001
- **Application method** : Apply two coats by roller, brush or spray onto clean, dry and sealed surface.
- **Dilution** : Thin down with water as required; for best results do not exceed the dilution volume ratio of 1 part water to 5 parts paint.
- **Spreading rate / Film thickness** : One litre of **MAUVINYL** will cover between 7 and 9 m² of surface in one coat ; at this spreading rate the dry film thickness will vary between 36 and 47 microns on a completely smooth, non absorbent surface.
- **Drying time** : Approximately 30 minutes to touch dry, **MAUVINYL** can be over-coated after approximately 3 hours.
- **Cleaning solvent** : Use water; if necessary add some liquid detergent to warm water.
- **Preceding coat** : Seal with **MAUVILAC CLEAR EMULSION BINDER** or **MAUVILITH SEALER** on new and on powdery or absorbent surfaces to get a sound surface for proper adhesion of **MAUVINYL**.
- **Subsequent coat** : Not required. To improve its resistance to cleaning and scrubbing **MAUVINYL** can be overcoated with one coat of **MAUVILAC CLEAR EMULSION FINISH**.

SAFETY

- **MAUVINYL** can be safely used in rooms that will be occupied the following day or where food stuff are stored or processed.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Manufactured and Distributed by:
Mauvilac Industries Ltd
 Pailles Road, Pailles, Republic of Mauritius
 Tel: (230) 206 4700
 Fax: (230) 286 5315

Jan 2004