



MAUVIPLAST

PRODUCT DATA SHEET

A TEXTURED PAINT FOR EXTERIOR USE

A high quality acrylic copolymer emulsion paint which dries quickly to give an attractive textured finish.

- **MAUVIPLAST** is available in white and in 6 colours.

MAUVIPLAST is a protective and highly decorative coating with maximum hiding power in one coat. It will cover and obliterate common surface defects such as fine cracks and irregularities to produce a uniform and pleasant textured finish. It is recommended for homes, offices, shops, factories, hotels and other related structures.

USAGE

- On cement substrates such as plaster, concrete and building blocks.
- On surfaces with fine cracks and irregularities.
- On sealed wooden surfaces.
- On suitably prepared galvanised steel panels.
- Recommended for exterior use but can just as well be used on interior surfaces.

PHYSICAL DATA

- **Product Code:** 0312
- **Finish :** Matt with medium granular texture
- **Colour :** White and 6 special colours
- **Consistency :** Viscous liquid
- **Specific Gravity :** 1.59 (approx.)
- **Volume Solids :** 62% (approx.)
- **Flash Point :** Not Applicable
- **Shelf Life :** 12 months
- **Packing :** 20 L, 5 L

APPLICATION

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information.

- **Surface preparation :** See method SP 001 (or SP 004 for Galvanised Steel)

- **Application method** : Apply one coat by roller onto clean, dry and sealed surface. USE A COARSE SPONGE ROLLER TO ACHIEVE A TEXTURED FINISH.
- **Dilution** : It is not necessary to thin down the paint for application, dilution will alter the texture characteristic. However, **MAUVIPLAST** can be diluted with water to suit your specific requirements.
- **Spreading rate / Film thickness** : One litre of **MAUVIPLAST** will cover between 2 and 4 m² of surface in one coat ; at this spreading rate the dry film thickness will vary between 310 and 155 microns on a completely smooth, non absorbent surface. **MAUVIPLAST** contains Silica Sand of various particle sizes, the film thickness at any given points will fluctuate accordingly.
- **Drying time** : Approximately 45 minutes to touch dry; **MAUVIPLAST** can be over-coated after approximately 8 hours.
- **Cleaning solvent** : Use water; if necessary add some liquid detergent to warm water.
- **Preceding coat** : On new and on powdery or absorbent surfaces, seal with one coat of **MAUVIPLAST PRIMER**.
- **Subsequent coat** : Not required.

SAFETY

- **MAUVIPLAST** can be safely used in rooms that will be occupied the following day or where food stuff are stored or processed.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

November 1998