



PATIO FLOOR SEALER

PRODUCT DATA SHEET

A solvent soluble ACRYLIC sealer for cement based porous tiles, slate, stone, wood and other absorbent materials usually used for patios.

PATIO FLOOR SEALER is an alkali resistant sealer with good penetrating properties. It is usually used to saturate absorbent surfaces to facilitate cleaning thereafter.

PATIO FLOOR SEALER is a penetrating sealer, do not use it as a surface varnish nor on previously coated surfaces unless such coatings have been completely removed.

USAGE

- On cement based and other tiles (polished stone, slates, etc ...) used for patios.
- On concrete parking and floor areas to prevent dusting and spalling.
- On wood.

PHYSICAL DATA

- **Product Code :** 1A3000
- **Finish :** Matt
- **Colour :** Clear
- **Consistency :** Free flowing liquid
- **Specific Gravity :** 0.80 - 0.90
- **Volume Solids :** 15% (approx.)
- **Flash Point :** 38 ° C (closed cup)
- **Shelf Life :** 12 months
- **Packing :** 5 L, 1L

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information

APPLICATION

- **Surface preparation:** Surfaces should be clean, free from oil, grease and contaminants.
- **Application method:** Apply one coat by roller or brush onto clean, and dry surfaces.
- **Dilution:** Ready for use. Dilute with **TEST BENZIN** if necessary.
- **Spreading rate / Film thickness:** One litre of **PATIO FLOOR SEALER** will cover between 10 and 15 m² of surface in one coat; at this spreading rate the dry film thickness will vary between 15 and 10 microns on a completely smooth, non absorbent surface.
- **Drying time:** Approximately 30 minutes to touch dry, **PATIO FLOOR SEALER** can be over-coated after approximately 6 hours.
- **Cleaning solvent :** **TEST BENZIN**
- **Preceding coat :** Not required.
- **Subsequent coat :** Not applicable.

SAFETY

- **PATIO FLOOR SEALER** is flammable, keep away from ignition source. Do not smoke whilst using.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.
- A complete Material Safety Data Sheet is available on request.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Manufactured and Distributed by:
Mauvilac Industries Ltd
 Pailles Road, Pailles, Republic of Mauritius
 Tel: (230) 206 4700
 Fax: (230) 212 4308

June 2007