



# WOOD PRIMER

## PRODUCT DATA SHEET

A good quality alkyd resin based general purpose primer for all types of wood.

- Available in Pink or Grey.

**WOOD PRIMER** applied directly onto the substrate will provide maximum adhesion between the substrate and subsequent coats. It is easy to apply and dries quickly to give good opacity and grain filling properties. **WOOD PRIMER** is recommended for use in Alkyd based paint systems.

### USAGE

- As a primer on all types on wood.
- On interior and exterior surfaces.

### PHYSICAL DATA

- **Product Code :** 0520 (Pink) , 0519 (Grey)
- **Finish :** Matt
- **Colour :** Pink or Grey
- **Consistency :** Semi viscous liquid
- **Specific Gravity :** 1.53 (approx.)
- **Volume Solids :** 55% (approx.)
- **Flash Point :** 38 °C (Closed cup)
- **Shelf Life :** 12 months
- **Packing :** 20 L, 5 L, 2 L, 1 L

Paints should be stirred before use and occasionally whilst in use.  
Contact your supplier for further information

### APPLICATION

- **Surface preparation** : See method SP 002.
- **Application method** : Apply one coat by roller or brush onto clean, dry surface. Low pressure or airless spray equipment can also be used.
- **Dilution** : Thin down with **TEST BENZIN** as required.
- **Spreading rate / Film thickness** : One litre of **WOOD PRIMER** will cover between 6 and 8 m<sup>2</sup> of surface in one coat ; at this spreading rate the dry film thickness will vary between 90 and 70 microns on a completely smooth, non absorbent surface.
- **Drying time** : Approximately 2 hours to touch dry, **WOOD PRIMER** can be over-coated after approximately 5 - 6 hours when cured in direct sunlight, otherwise allow to cure overnight.
- **Cleaning solvent** : Test Benzin.
- **Preceding coat** : Not required.
- **Subsequent coat** : **UNIVERSAL UNDERCOAT** .

#### **SAFETY**

- **WOOD PRIMER** is flammable, keep away from ignition source. Do not smoke whilst using.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.
- A complete Material Safety Data Sheet is available on request.

#### **MAINTENANCE**

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Manufactured and Distributed by  
**Mauvilac Industries Ltd**  
 Pailles Road, Pailles, Republic of Mauritius  
 Tel: (230) 206 4700  
 Fax: (230) 286 5315

Jan 2004